



# INNOVATOR 716



## INNOVATOR 716 Moldboard Plow

*A Deeper, Faster Plowing Experience*

The FIM **Innovator 716** Moldboard Plow gives you full adjustability for plowing depth, while the pivoting design lets you reverse the moldboards to make right- and left-hand-side passes to help finish plowing faster. Using larger-horsepower tractors, the on-land **Innovator 716** gives you maximum productivity in a variety of sizes.



### SAFETY-TRIP SYSTEM

The safety-trip system is fully adjustable to allow for plowing in rocky or hard ground conditions while keeping the operator inside the tractor. When the tripping mechanism engages, raise the plow and the bottom will reset itself.



### V-STYLE MAINFRAME

The **Innovator 716** V-style mainframe distributes weight for better penetration. It is designed to handle the stress of high-horsepower tractors working in tough ground conditions.

Model	Innovator 716
<b>SIZES</b>	6, 7, 8 Bottom
<b>MAINFRAME</b>	6, 7, 8 Bottom: 6x8 in. x 1/2 in. thick
<b>UNDERFRAME CLEARANCE</b>	39 in.
<b>WIDTH OF CUT</b>	24 in.
<b>HITCH</b>	Category 3 & 4 Quick Hitch Compatible
<b>TYPE OF REVERSING</b>	Hydraulic Cylinder
<b>STANDARDS</b>	Welded, Tubular Frame Safety Trip Mechanism Adjustable Rear Gauge Wheel Powder Coated Finish
<b>TYPE OF PROTECTION</b>	Safety Trip (Standard)
<b>TOTAL WIDTH OF CUT (APPROXIMATE)</b>	6-Bottom: 10 ft. 6 in. 7-Bottom: 12 ft. 6 in. 8-Bottom: 14 ft. 6 in.
<b>MAXIMUM PLOWING DEPTH</b>	21 in.
<b>WEIGHT (APPROXIMATE)</b>	6-Bottom: 5,180 lbs. 7-Bottom: 6,040 lbs. 8-Bottom: 6,900 lbs.
<b>HP REQUIRED*</b>	6-Bottom: 225+ hp 7-Bottom: 275+ hp 8-Bottom: 300+ hp

\*The required horsepower is an estimation only. Required horsepower is dependent on many factors including soil type, hardness, depth of cut, etc.

**Call 432-758-0068**  
to locate your area dealer today!

Email us at [info@fimtx.com](mailto:info@fimtx.com) for more information.